

Click on products for more information

5-6 Watts	10-12 Watts	12-18 Watts	18-24 Watts	30-36 Watts	40-60 Watts	60-70 Watts	90-150 Watts	240-800 Watts
<p><b>GT-83083-0505-USB</b> 5 Watts Vout=5 49.2 x 47.0 x 27.5</p>	<p><b>GT-83084-10VV-USB</b> 10 Watts Vout=5-5.2 51.5 x 23.5 x 38.5 +/-0.3</p>	<p><b>GT-46120-12VV-X.X</b> 12 Watts Vout=5-48 64.0 x 40.5 x 31.5</p>	<p><b>GTM96180-18VV</b> 18 Watts Vout=4-48 74 x 43.5 x 36.8</p>	<p><b>GTM91120-30VV-FW</b> 30 Watts Vout=5-48 102 x 46 x 37</p>	<p><b>GT-46401-40VV-X.X-Q</b> 40 Watts Vout=12-48 90.0 x 38.0 x 59.4</p>	<p><b>GTM43007-AWVVV-F</b> 60 Watts Vout=5-48 76.2 x 50.8 x 23.6 with heat sink 76.2 x 50.8 x 22.5 without heat sink</p>	<p><b>GTM96900P90VV-X.X</b> 90 Watts Vout=12-54 149.38 x 62.6 x 33.5 +/--1.0</p>	<p><b>GTM91110P240XX</b> 240 Watts Vout=12-55 127 x 76 x 43</p>
<p><b>GTM96060-06VV-Q</b> 6 Watts Vout=3.3-48 43.5 x 74.0 x 36.8</p>	<p><b>GT-86120-WVVV</b> 10 Watts Vout=5, 12 70(L) x 32.8(W) x 48.5(H)</p>	<p><b>GT-86120-WVVV-X.X-W2E</b> 12 Watts Vout=5, 12 69 x 28.8 x 58.3</p>	<p><b>GTM41080-18VV-F</b> 18 Watts Vout=5-48 74 x 44 x 34</p>	<p><b>GTM91120CC-30VV-P2</b> 30 Watts Vout=5-48</p>	<p><b>GT-46400-40VV-X.X</b> 40 Watts Vout=12-48 111 x 52 x 32.3</p>	<p><b>GTM43007-BWVVV-F</b> 60 Watts Vout=5-48 101.6 x 50.8 x 22.5</p>	<p><b>GTM961200P-120VV</b> 120 Watts Vout=12-54 149.30" x 62.80 x 34.0</p>	<p><b>GTMG3078P350VV-X.X-FW</b> 350 Watts Vout=12-48 76.2 x 39.6 x 127</p>
<p><b>GT-46060-06VV-X.X-Q</b> 6 Watts Vout=5-24 40.5 x 64.0 x 30.0</p>	<p><b>GTM46101-10VV-X.X-USB</b> 10 Watts Vout=5-5.5 41.0 x 71.0 x 31.5</p>	<p><b>GTM46161-16VV-X.X-USB</b> 16 Watts Vout=5-5.5 41.0 x 71.0 x 31.5</p>	<p><b>GTM93021-20VV-P2</b> 20 Watts Vout=5-48</p>	<p><b>GT-83082-3612-W2/W2E</b> 36 Watts Vout=12 93 x 33 x 78.69 +/-0.5</p>	<p><b>GTM96600-60VV</b> 60 Watts Vout=5-54 117.5 x 53.5 x 34.2</p>	<p><b>GTM91099-60VV-P3</b> 60 Watts Vout=5-48</p>	<p><b>GTM43004P-WVVV-X.X-F</b> 120 Watts Vout=5-48 184.0 X 62.0 X 37.5</p>	<p><b>GTMG3079P450VV-X.X-F</b> 450 Watts Vout=12-48 101.6 x 39.6 x 177.8</p>
<p><b>GT-86060-06VV-X.X-W2</b> 6 Watts Vout=5, 12 66.5 x 25.5 x 51.3</p>	<p><b>GT-86120-WVVV-X.X-W2C</b> 12 Watts Vout=5, 12 69 x 28.8 x 40.3</p>	<p><b>GT-96180-1856-R2-AP</b> 18 Watts Vout=56</p>	<p><b>GT-46240-24VV</b> 24 Watts Vout=12-24 80.6 x 50.0 x 31.0</p>	<p><b>GTM96300-36VV-R2/R3A</b> 36 Watts Vout=5-48 74 x 43.5 x 36.8</p>	<p><b>GTM96600-60VV-R</b> 60 Watts Vout=5-48 117.53 x 53.47 x 36.6</p>	<p><b>GT-96600-7056-T3-AP</b> 70 Watts Vout=56</p>	<p><b>GTM43004P-WVVV-X.X-P3</b> 120 Watts Vout=5-48</p>	<p><b>GT-G3068P650VV-X.X-C</b> 650 Watts Vout=5-48 127 x 40.9 x 249</p>
<p><b>GTM41134-WVVV-F</b> 6 Watts Vout=3.3-48 84.5 x 41.5 x 17.0</p>	<p><b>GT-86120-WVVV-X.X-W2</b> 12 Watts Vout=5, 12 69 x 28.8 x 40.3</p>	<p><b>GTM96180-18VV</b> 18 Watts Vout=5-48</p>	<p><b>GT-86240-WVVV-X.X</b> 24 Watts Vout=12 73.5 x 35 x 57</p>	<p><b>GT-96300-3656-AP</b> 36 Watts Vout=56 107 x 55 x 36</p>	<p><b>GTM95600-BWVVV-F</b> 60 Watts Vout=5-48 101.6 x 50.8 x 30.5</p>	<p><b>GTM96700-BWVVV-F</b> 70 Watts Vout=5-48 101.6 x 50.8 x 30.5</p>	<p><b>GTM961500P-150VV</b> 150 Watts Vout=12-54 173 x 72 x 38</p>	<p><b>GT-G3062P800VV-X.X-C</b> 800 Watts Vout=12-60 127 x 41 x 249</p>

Click on products for more information

1000-3000 Watts	Battery Packs		International Power Cords			
 <p><b>GT-G3064P1000VV-X.X-C</b> 1000 Watts Vout=12-48 127 x 40.9 x 283</p>	<p><b>BL0105F2635161S1PCAT</b> Lithium Polymer 3.7VDC, 105mAh Battery Pack Dimensions: 2.8 x 16.5 x 37 Configuration: 1S 1P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified</p> 	<p><b>BL1880F6835661S5PX9M</b> Lithium Polymer 3.7VDC, 9400mAh Battery Pack Dimensions: 185.5 x 69.5 x 7.9 mm 10K NTC Thermistor BQ27200 Configuration: 1S 5P Cell Type: GP683566 Cell Shape: Rectangular IEC 62133 Certified</p> 	<p><b>Type 451</b> North America NEMA 1-15P 10A, 13A/125V~</p> 	<p><b>Type 302</b> North America NEMA 5-15P 10A, 13A/15A/125V~</p> 	<p><b>Type 119</b> North America NEMA 5-15P Hospital Grade 10A, 13A/15A/125V~</p> 	<p><b>Type 703</b> IEC 60320-C7 2.5A/250V~</p> 
 <p><b>GTMG3073P1200VV-X.X</b> 1200 Watts Vout=12-60</p>	<p><b>BL0750F5030481S1PCMC</b> Lithium Polymer 3.7VDC, 700mAh Battery Pack Dimensions: 50.5 x 30.5 x 5.3 10K NTC Thermistor Configuration: 1S 1P Cell Type: GP503048 Cell Shape: Rectangular IEC 62133 Certified UL 2054 Certified</p> 	<p><b>Custom Battery Packs</b> Contact GlobTek with your specifications</p> 	<p><b>Type 701</b> IEC 60320-C13 10A, 13A, 15A 125V~, 250V</p> 	<p><b>Type 712</b> IEC 60320-C5 2.5A, 10A/250V~</p> 	<p><b>Type 7033</b> IEC 60320-C19 12A, 14A, 16A 125~250V</p> 	<p><b>Type 705</b> IEC 60320-C14 10A, 13A, 15A/250V~</p> 
 <p><b>GT-G3060P1500VV-X.X-C</b> 1500 Watts Vout=12-60</p>	<p><b>BL1200P4054481S1PCAC</b> Lithium Polymer 3.7VDC, 1200mAh Battery Pack Dimensions: 53.0 x 48.0 x 4 10K NTC Thermistor Configuration: 1S 1P Cell Type: GP404852 Cell Shape: Rectangular IEC 62133 Certified</p> 	<p><b>BL2600C1865004S1PXX</b> Lithium Ion 14.8VDC, 2600mAh Battery Pack Dimensions: 77 x 69 Fuel Gauge Configuration: 4S 1P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified</p> 	<p><b>Type PZ0800</b> United Kingdom BS1363 13A/250V~</p> 	<p><b>Type 207</b> "Europlug" CEE7 Standard XVI (CEE 7/16) 2.5A/250V</p> 	<p><b>Type 2314</b> Schuko Europe CEE7 Standard sh 7 16A/250V</p> 	<p><b>Type 550</b> Australia, New Zealand AS/NZS 3112 10A/250V~</p> 
 <p><b>GT-G3063P3000VV-X.X-HV-C</b> 3000 Watts Vout=150-400</p>	<p><b>BL2200F6034501S2XXXX</b> Lithium Ion 3.7VDC, 2200mAh Battery Pack Dimensions: 51 x 34 x 13 Configuration: 1S 2P Cell Type: 603450 Cell Shape: Rectangular IEC 62133 Certified</p> 	<p><b>BL2600C1865004S1PG1</b> Lithium Ion 14.8VDC, 2600mAh Battery Pack Dimensions: 66 x 73.5 x 28.5 Fuel Gauge/Built In Charger Circuitry 4S 1P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified</p> 	<p><b>Type 205</b> India IS 1293 6A/250V~</p> 	<p><b>Type 208</b> South Africa SABS 164-1 16A/250V~</p> 	<p><b>Type 219</b> Argentina IRAM 2073 10A/250V~</p> 	<p><b>Type 204B</b> Brazil NBR 14136 10A/250V~</p> 
 <p><b>Custom Power Supplies</b> 1-3000 Watts</p>	<p><b>BL2600C1865001S2PXXXX</b> Lithium Ion 3.7VDC, 5200mAh Battery Pack Dimensions: 19 x 68.5 x 37 Configuration: 1S 2P Cell Type: ICR18650-26F Cell Shape: Cylindrical IEC 62133 Certified</p> 	<p><b>GTM91128</b> Smart Battery Charger Available in versions delivering 4.2V, 8.4V, or 12.6V at 1 A to address single- or multiple-battery configurations</p> 	<p><b>Type 602</b> China GB 1002 10A/250V~</p> 	<p><b>Type 377C</b> Israel 16A/250V~</p> 	<p><b>Type 2302</b> Italy CEI 23-16 10A/250V~</p> 	<p><b>Type 2313K</b> Korea KS C 8305 16A/250V~</p> 